



US009636693B2

(12) **United States Patent**
Nakano et al.

(10) **Patent No.:** **US 9,636,693 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **METHOD AND APPARATUS OF
MANUFACTURING EXHAUST
GAS-PURIFYING CATALYST AND NOZZLE
USED THEREFOR**

(71) Applicant: **CATALER CORPORATION,**
Shizuoka (JP)

(72) Inventors: **Atsushi Nakano**, Shizuoka (JP);
Shigeki Mizuno, Shizuoka (JP); **Shigeji**
Matsumoto, Shizuoka (JP); **Hiroshi**
Sekine, Shizuoka (JP); **Suguru Matsui**,
Shizuoka (JP)

(73) Assignee: **CATALER CORPORATION,**
Shizuoka (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/945,185**

(22) Filed: **Nov. 18, 2015**

(65) **Prior Publication Data**

US 2016/0067720 A1 Mar. 10, 2016

Related U.S. Application Data

(60) Division of application No. 13/251,761, filed on Oct.
3, 2011, now Pat. No. 9,227,184, which is a
(Continued)

(30) **Foreign Application Priority Data**

Apr. 3, 2009 (JP) 2009-091140
Jan. 25, 2010 (JP) 2010-013568

(51) **Int. Cl.**

B05B 1/14 (2006.01)

B05B 12/02 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **B05B 1/14** (2013.01); **B01J 35/04**
(2013.01); **B01J 37/0215** (2013.01);
(Continued)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,057,190 A 11/1977 Kiwior et al.

4,544,446 A 10/1985 Cady

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1900442 A1 3/2008

JP 2-40241 2/1990

(Continued)

OTHER PUBLICATIONS

International Search Report mailed by the International Searching
Authority (ISA/JP) on Jul. 13, 2010 in connection with PCT
International Application No. PCT/JP2010/056098, filed Apr. 2,
2010.

(Continued)

Primary Examiner — Dah-Wei D Yuan

Assistant Examiner — Jethro M Pence

(74) *Attorney, Agent, or Firm* — John P. White; Cooper &
Dunham LLP

(57) **ABSTRACT**

A nozzle is configured to discharge a fluid containing a raw
material of a catalytic layer to a substrate having first and
second end faces and provided with holes each extending
from the first end face to the second end face. The nozzle is
provided with discharge ports each discharging the fluid
toward the first end face of the substrate.

14 Claims, 16 Drawing Sheets

